QUICKSTART FOR WEB DEVELOPERS

LET’S GO

1. Get a free Creator Access. Log in to ShowMoor Web App.
2. Select SM Button or SM Cooin from Creator menu.

Earn from subscriptions.

Earn from one-time payments.

3. Customize SM Code by filling in the SM Code settings.
4. Generate SM Code and insert it to your webpages.

SM CODE

SM Code is plain JavaScript.

SM Code contains your customizations and ShowMoor functionality.

SM Code is obfuscated to hinder its tampering.

SM Code execution starts on DOMContentLoaded event.

RE: SM CODE SETTINGS FOR BUTTONS

```
async function yesShowMoor() {
// This is executed for those who have ShowMoor subscription
// and have clicked the SM Button at least once.
}
async function noShowMoor() {
// This is executed for those who do not have a subscription
// or have not clicked the SM Button.
}
```

ShowMoorSID is an MD5 based on your user ID number and salt. It is visible on SM Code settings page, and added to the localStorage.showmoor_sid for subscribers.

RE: SM CODE SETTINGS FOR COOINS

```
async function paidWithCooin() {
// This is executed for those who have paid for the content.
// ShowMoorXID is generated here.
}

async function notPaidWithCooin() {
// This is executed if the content has not been paid.
}
```

ShowMoorXID is a SHA256 derived from page URL (hostname + pathname), your user ID number, salt and an optional showmoor_ct parameter. SM Code settings page has a link to a tool that calculates it.

MISC

Remember to add link to ShowMoor CSS in your files.

```
<link rel="stylesheet" href="https://showmoor.com/sm_css/sm001.css">
```

SM Code uses the CSS to create Button and Cooin elements.

ShowMoorCOLOR variable contains the Button/Cooin color.

The Web App has SM Code examples for you to build on.

The SM Code page has the latest tips and tricks in detail.

YOUR FEEDBACK IS APPRECIATED

Questions/comments/rants/raves…

Drop’em here:
tomi@showmoor.com